


Product: [8471NH](#) 

Electronic, 1PR #16 Str TC, PO ins, Unsh, LSNH Jkt, 300V



 [Request Sample](#)

Product Description

Electronic, 1 Pair AWG 16 Tinned Copper - Stranded, Polyolefin (PO, PE, PP) insulation, Unshielded shielding, LSZH / FRNC jacket , 300V

Technical Specifications

Product Overview

Environmental Space:	Indoor - Euroclass B2ca
Suitable Applications:	Instrumentation and computer cable; For data transmission applications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Pairs
16	19x29	TC - Tinned Copper	1

Conductor Count:	2
Total Number of Pairs:	1

Insulation

Material	Nominal Diameter	Diameter +/- Tolerance	Nominal Wall Thickness
FRPE - Flame Retardant Polyethylene	2.67 mm	0.05 mm	0.018 in

Color Chart

Number	Color
Pair 1	Black & White

Inner Shield Material

Material
Unshielded

Inner Jacket Material

Nominal Wall Thickness
0.89 mm

Outer Shield Material

Material
Unshielded

Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
LSZH / FRNC (UV stabilised)	7.1 mm	0.89 mm

Construction and Dimensions

Stranding

Twists
6 twist/ft

Cabling

Description
1 pair covered with a polyester foil

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR
14.7 Ohm/km

Capacitance

Nom. Capacitance Conductor to Conductor
52 pF/m

Inductance

Nominal Inductance	Nominal Pair Inductance
0.17 µH/ft	0.62 µH/m

Current

Element	Max. Recommended Current [A]
Conductor	7.1 A

Voltage

UL Voltage Rating	Voltage Rating [V]
300 V RMS	300 V

Temperature Range

Installation Temp Range:	-15°C To +80°C
Storage Temp Range:	-45°C To +80°C
Operating Temp Range:	-20°C To +75°C
Operating Temp Range (Flexible Install):	-15°C To +80°C
Operating Temp Range (Fixed Install):	-45°C To +80°C

Mechanical Characteristics

Oil Resistance:	IEC 60811-404
Bulk Cable Weight:	32 lbs/1000ft
Max Recommended Pulling Tension:	127 N
Min Bend Radius During Installation:	71 mm
Min Bend Radius/Minor Axis:	2.5 in

Standards

NEC/(UL) Specification:	CMG
CEC/C(UL) Specification:	CMG
CPR Euroclass:	B2ca-s1,d1,a1
CENELEC Compliance:	EN 50290-2-27
Other Specification:	BS 7655 section 6.1 table 1, LTS 3

Applicable Environmental and Other Programs

EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-01-01

Suitability

Suitability - Indoor:	Yes
Suitability - Non-Halogenated:	Yes

Flammability, LS0H, Toxicity Testing

C(UL) Flammability:	FT4
UL Flammability:	UL1685 FT4 Loading
ISO/IEC Flammability:	IEC 60332-1-2 and IEC 60332-3-24

Amount of Halogen acc. to IEC 60754-1 & EN50267-1: Zero
UL voltage rating: 300 V RMS

Plenum/Non-Plenum

Plenum (Y/N): No

Part Number

Variants

Item #	Color	Length
8471NH.01500	Blue	500 m
8471NH.001000	Chrome	1,000 m
8471NH.001500	Chrome	1,500 m
8471NH.00152	Chrome	152 m
8471NH.00305	Chrome	305 m
8471NH.00500	Chrome	500 m
8471NH.K01000	Chrome	1,000 m
8471NH.K0305	Chrome	305 m
8471NH.K0500	Chrome	500 m
8471NH.021000	Green	1,000 m
8471NH.031000	White	1,000 m
8471NH.03500	White	500 m

History

Update and Revision: Revision Number: 0.248 Revision Date: 01-31-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.