

I			
1			
		In.	
	8		

Product: <u>70006E</u> ☑

DataTuff® 5E, 1Q #22 Sol BC, PO ins, F/B, PVC jkt, PROFINET type A, AWG 2464

Request Sample

Product Description

DataTuff® 5E, 1 Quad AWG 22 Bare Copper - Solid, Polyethylene insulation, SF/UTP - Overall Braid + Foil shielding, PVC jacket , PROFINET type A, AWM 2464

Technical Specifications

Product Overview

Suitable Applications:	PROFINET, harsh environment, IIoT, factory or process automation, IP cameras and devices, data communication, etc	

Construction Details

Conductor

Size	Stranding	Material	Number of Pairs	Number of Element
22 AWG	Solid	BC - Bare Copper	2	4

Insulation

Material	Nom. Insulation Diameter	Color Code
PE - Polyethylene	1.5 mm (0.059 in)	White & Blue & Yellow & Orange
		1 Quad

Cable Core

Description

1 quad with center filler

Inner Jacket

Material		Nom. Diameter
LSZH - Low Smoke Zero Halogen (Flame Retardant)		3.9 mm (0.15 in)
Table Notes: Bedding		

Outer Shield

Shield Type	Material	Coverage
Таре	Bi-Laminate (Alum+Poly)	
Braid	Tinned Copper (TC)	85%

Outer Jacket

Material	Nom. Diameter
PVC - Polyvinyl Chloride	6.5 mm (0.26 in)
Overall Cable Diameter (Nominal): 6.5 mm

Electrical Characteristics

Electricals

Max. Conductor DCR	Nom. Characteristic Impedance
57.1 Ohm/km	100 Ohm

Delay

Max. Delay Nom. Velocity of Prop.

530 ns/100m 68%

High Frequency

Frequency [MHz]	Max. Insertion	Loss (Attenuation)	Min. NEXT [dB]	Min. ACRF (ELFEXT) [dB]	Min. SRL (Structural Return Loss) [dB]
1	2.1 dB/100m		65.3	64	
4	4.1 dB/100m		56.3	52	23
10	6.5 dB/100m		50.3	44	25
16	8.3 dB/100m		47.2	40	25
31.25	11.7 dB/100m		42.9	34	23.6
62.5	17 dB/100m		38.4	28	21.5
100	22 dB/100m		35.3	24	20.1
Table Notes:		Reference standard:	ISO/IEC 11801 e	d 2.0, Cat 5e	

Transfer Impedance

Frequency	Max. Transfer Impedance
10 M/h=	Max 10 mcOhme/m

10 Mhz Max. 10 mOhm/m

Voltage

Voltage Rating 300 V

Mechanical Characteristics

Temperature				
Operating	Installation	Storage		
-40°C to +80°C	-5°C To +60°C	-40°C to +80°C		

Standards and Compliance

Environmental Suitability:	Indoor - Euroclass Eca, Indoor, Oil Resistance	
Flammability / Reaction to Fire:	IEC 60332-1-2	
CPR Compliance:	CPR Euroclass: Eca	
AWM Compliance:	AWM 2464	
Data Category:	Category 5e	
ISO/IEC Compliance:	ISO/IEC 11801-1	
European Directive Compliance:	EU CE Mark	

History

Update and Revision:

Revision Number: 0.253 Revision Date: 12-15-2021

Variants

Item #	Color	Putup Type	Length	EAN
70006E.01B100	Green	Flat Box	100 m	8719605009227
70006E.01305	Green	Reel	305 m	8719605009203
70006E.01500	Green	Reel	500 m	8719605009210
70006E.011000	Green	Reel	1,000 m	8719605009197
70006E.013000	Green	Reel	3,000 m	8719605167026

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.