



Product: [CAT5E KEYCONNECT JACKS](#) 

CAT5E Modular Jack, RJ45, KeyConnect Style

Product Description

CAT5E KeyConnect Jacks are available in several colors.

Technical Specifications

Product Overview

Environmental Space:	Indoor
Suitable Applications:	IBDN System 1200, TIA Category 5E, ISO Class D, 1000 BASE-T

Physical Characteristics (Overall)

Height:	0.88 in
Width:	0.64 in
Depth:	1.29 in
Wiring Scheme:	T568A/B
Packaging:	Individually packaged in a plastic bag. Standard pack of 50 units.
Weight:	0.014 lbs

Connectors

Materials

Description	Material	Type
Front Connection	Copper Alloy with 50 μ inch Gold over Nickel	Lead Frame
Rear Connection	Copper Alloy with Nickel Plating	IDC
Connector Body	Plastic - UL940V-0	

Electrical Characteristics

Dielectric Strength:	1,000V RMS @ 60 Hz for 1 minute
Current Rating:	1.500 A
Insulation Resistance:	500 M-Ohm Minimum
Max Contact Resistance:	20 mOhm
Termination Resistance:	2.5 mOhm

Temperature Range

Installation Temp Range:	-10°C to +60°C
Storage Temp Range:	-40°C to +70°C
Operating Temp Range:	-10°C to +60°C

Mechanical Characteristics

Footprint/Type:	KeyConnect
Tool Compatibility:	Belden 110 Connecting Tool, MediaFlex Termination Station
Plug /Jack Compatibility:	RJ45, RJ11
Termination Front Connection:	Mated Connection
Termination Front Connection Durability:	1,000 cycles

Termination Rear Connection:	Gas Tight IDC Connection
Termination Rear Connection Durability:	20 terminations
Connector/Hardware Retention:	20 lbs
Plug/Connector Retention:	11.250 lbs

Standards

Data Category:	Category 5e
Telecommunications Standards:	Category 5 - ISO/IEC 11801:2002 Ed.2
Other Standards:	FCC Part 68, Subpart F, IEC 60603-7
Third Party Performance Verification:	ETL - Verified Category 5e

Applicable Environmental and Other Programs

EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2006-07-01
MII Order #39 (China RoHS):	EUP 50

Flammability, LS0H, Toxicity Testing

Safety Listing:	ACA, c(UL)us Listed
-----------------	---------------------

Part Number

Related Parts:	Compatible with KeyConnect Faceplates, Adapters, Boxes and Patch Panels
----------------	---

Variants

Item #	Color	Packaging	Wiring Scheme
AX101308	Almond	Single Pack	T568A/B
AX101308-B24	Almond	Bulk Pack (24)	T568A/B
AX101310	Black	Single Pack	T568A/B
AX101310-B24	Black	Bulk Pack (24)	T568A/B
AX104186	Blue	Single Pack	T568A/B
AX104186-B24	Blue	Bulk Pack (24)	T568A/B
AX104188	Brown	Single Pack	T568A/B
AX104188-B24	Brown	Bulk Pack (24)	T568A/B
AX101309	Electric White	Single Pack	T568A/B
AX101309-B24	Electric White	Bulk Pack (24)	T568A/B
AX101307	Gray	Single Pack	T568A/B
AX101307-B24	Gray	Bulk Pack (24)	T568A/B
AX104185	Green	Single Pack	T568A/B
AX104185-B24	Green	Bulk Pack (24)	T568A/B
AX103079	Ivory	Single Pack	T568A/B
AX103079-B24	Ivory	Bulk Pack (24)	T568A/B
AX104182	Orange	Single Pack	T568A/B
AX104182-B24	Orange	Bulk Pack (24)	T568A/B
AX104187	Purple	Single Pack	T568A/B
AX104187-B24	Purple	Bulk Pack (24)	T568A/B
AX104183	Red	Single Pack	T568A/B
AX104183-B24	Red	Bulk Pack (24)	T568A/B
AX101315	TIA Blue	Single Pack	T568A/B
AX101317	TIA Brown	Single Pack	T568A/B
AX101314	TIA Green	Single Pack	T568A/B
AX101311	TIA Orange	Single Pack	T568A/B
AX101316	TIA Purple	Single Pack	T568A/B
AX101312	TIA Red	Single Pack	T568A/B
AX101313	TIA Yellow	Single Pack	T568A/B
AX104184	Yellow	Single Pack	T568A/B
AX104184-B24	Yellow	Bulk Pack (24)	T568A/B

Product Notes

Included Parts:	1 T-Bar
Notes:	Please see Installation Guide PX103329

History

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.