


Product: [MRG2130](#) 

COAX RF RG 213 PVC



Product Description

COAX RF RG 213 PVC

Technical Specifications

Product Overview

Suitable Applications:	Coaxial cable used in cable broadband communication networks designed according to the European Standard EN 50117-1; Operating at frequencies between 5 MHz and 3000 MHz; Designed for in building applications
------------------------	---

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Construction n x D	Nominal Diameter	Diameter +/- Tolerance	No. of Coax
13	Stranded	BC - Bare Copper	7x0.75 mm	2.25 mm	0.03 mm	1

Conductor Count: 1

Insulation

Type	Material	Nominal Diameter	Diameter +/- Tolerance
Dielectric	PE - Polyethylene	7.25 mm	0.2 mm

Outer Shield Material

Type	Material	Coverage [%]	Nominal Diameter	Diameter +/- Tolerance	Coverage +/- Tolerance
Braid	Bare Copper (BC)	92%	8 mm	0.25 mm	5%

Outer Jacket Material

Material	Nominal Diameter	Diameter +/- Tolerance
PVC - Polyvinyl Chloride	10.3 mm	0.3 mm

Construction and Dimensions

Min Elongation at Breakof Jacket:	150 %
Min Tensile Strength of Jacket:	12.5 MPa

Electrical Characteristics

Conductor DCR

Max. Conductor DCR	Max. Shield DCR
6 Ohm/km	5.5 Ohm/km

Capacitance

Nom. Capacitance	Capacitance Tolerance
100 pF/m	3 pF/m

Impedance

Nominal Characteristic Impedance	Nominal Characteristic Tolerance	Regularity of Impedance
50 Ohm	2 Ohm	Min. 46 dB

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
5 MHz	1.5 dB/100m
50 MHz	4.6 dB/100m
100 MHz	6.6 dB/100m
230 MHz	10.4 dB/100m
400 MHz	14.1 dB/100m
800 MHz	21.1 dB/100m
862 MHz	22.1 dB/100m
1000 MHz	24.1 dB/100m
1350 MHz	29 dB/100m
1750 MHz	34.3 dB/100m
2150 MHz	39.1 dB/100m
2400 MHz	42.4 dB/100m

Delay

Nominal Velocity of Propagation (VP) [%]
66%

High Freq

Frequency [MHz]	Min. RL (Return Loss) [dB]
100 - 400 MHz	28.5 dB
400 - 900 MHz	23.5 dB

Table Notes: In each frequency band, 3 peak values up to 4 dB lower are allowed

Voltage

Voltage Test Dielectric
3.0 kV DC

Temperature Range

Installation Temp Range:	-5°C To +50°C
Storage Temp Range:	-40°C To +70°C
Operating Temp Range:	-40°C To +70°C

Mechanical Characteristics

Min Bend Radius (W/o Pulling Strength):	50 mm
---	-------

Standards

IEC Compliance:	IEC 1196
CPR Euroclass:	Eca
CENELEC Compliance:	EN 50117-2-1, EN 50117-1 and EN 50290-2-20
RG Type:	213

Applicable Environmental and Other Programs

Environmental Space:	Indoor - Euroclass Eca
EU RoHS Compliance Date (yyyy-mm-dd):	1998-01-01

Flammability, LSOH, Toxicity Testing

IEC Flammability:	IEC 60332-1-2
-------------------	---------------

Part Number

Variants

Item #	Color	Putup Type	Length	EAN
MRG2130.00100	Black	Reel	100 m	8719605102942
MRG2130.00102	Black	Reel	102 m	8719605102966
MRG2130.00250	Black	Reel	250 m	8719605102973
MRG2130.00252	Black	Reel	252 m	8719605102980
MRG2130.00305	Black	Reel	305 m	8719605102997
MRG2130.00500	Black	Reel	500 m	8719605103000
MRG2130.01500	Black	Reel	500 m	8719605103017

MRG2130.02500	Black	Reel	500 m	8719605103024
MRG2130.001000	Black	Reel	1,000 m	8719605102959

History

Update and Revision: Revision Number: 0.166 Revision Date: 06-24-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.