	<b>TECHNICAL DATA SHEET</b>	code	<b>YE01823</b>
		version	<b>3</b>
		date	<b>2013-02-28</b>
	<b>4300FE NON-PAIRED</b>	page	<b>1/2</b>

## APPLICATION

Commercial applications shielded

## CONSTRUCTION



### 1. Conductor

Diameter of conductor  
Material

1.22mm (AWG18)  
stranded bare copper (7xAWG26)

### 2. Insulation

Material  
Diameter over insulation  
Wall thickness

PE  
1.72 ± 0.05 mm  
0.2 mm

### 3. Overall Cabling

Colour code

black – white

### 4. Outer shield


Shield  
Shield Material  
Shield Thickness Alu  
Shield coverage  
Drainwire

Beldfoil®  
Aluminium / Polyester tape  
9 µm  
100%  
AWG20 (7xAWG28) tinned Cu

### 4. Sheath

Material  
Colour  
Nominal thickness  
Nominal diameter

FRNC  
Gray or Blue  
0.38 mm  
4.40 mm

	<b>TECHNICAL DATA SHEET</b>	code	<b>YE01823</b>
		version	<b>3</b>
		date	<b>2013-02-28</b>
	<b>4300FE NON-PAIRED</b>	page	<b>2/2</b>

## REQUIREMENTS AND TEST METHODS

### Electrical:

Nominal resistance conductor	21.3 $\Omega$ /km
Nominal resistance shield	23.6 $\Omega$ /km
Nom. capacitance conductor to conductor @ 1kHz	125 pF/m
Nom. capacitance cond. to shield + other cond. @ 1kHz	224 pF/m
Test voltage conductor-conductor	2500 VDC, 3 seconds
Test voltage conductor-screen	2500 VDC, 3 seconds
Voltage rating	300 V RMS
Maximum continues current per conductor @ 25 °C	3.5 A per conductor @ 25 °C

### Mechanical and physical:

Temperature range processing and operating	-20 to +70 °C
Temperature range storage	-30 to +70 °C
Minimum bending/setting radius	5*D/10*D
Maximum pulling tension	26 N
Halogen free according to	IEC 60754-1
Non dense smoke according to	IEC 61034-1 and 61034-2
Non corrosive gas according to	IEC 60754-2
Flame Retardant according to	IEC 60332-1



Belden declares this product to be in compliance with the environmental regulations EU RoHS (Directive 2002/95/EC, 27 January 2003); this is valid for all material produced after the RoHS compliant date for this product.