




Product: [7785A](#)

Life Cycle Status: Discontinued



7785A - Triax 14, 11 AWG Str SPC, SPC + BC Braids, PVC Jkt

Product Description

Triax 14, 11 AWG (7x21) Stranded Silver plated Copper Conductor, PE Insulation, 80% Silver plated Copper Braid Shield, PE Insulation, 80% Bare Copper Braid Shield, PVC Jacket.

Technical Specifications

Product Overview

Suitable Applications:	Analog Video; Interconnect camera to CCU (camera control unit)
------------------------	--

Construction Details

Series Type:	Triax 8/11/14
--------------	---------------

Conductor

No. of Elements	Size	Stranding	Nom. Diameter	Material
1	12 AWG	Stranded	2.2 in	SC - Silvered Copper

Insulation

Element	Material	Nom. Insulation Diameter
Insulated Conductor	PE - Polyethylene (Foam)	9.7 mm (0.38 in)

Inner Shield

Shield Type	Material	Coverage
Braid	Silvered Copper (SC)	80%

Inner Jacket

Material	Nom. Diameter
PE - Polyethylene	11.9 mm (0.469 in)

Outer Shield

Outer Shield Type	Material	Coverage
Braid	Bare Copper (BC)	80%

Outer Jacket

Material	Nom. Diameter
PVC - Polyvinyl Chloride	14.5 mm

Electrical Characteristics

Attenuation

Frequency	Nom. Attenuation
1 MHz	0.4 dB/100m
10 MHz	1.3 dB/100m
20 MHz	1.7 dB/100m
40 MHz	2.5 dB/100m
50 MHz	2.8 dB/100m
60 MHz	3.1 dB/100m
100 MHz	4.2 dB/100m

270 MHz	7 dB/100m
300 MHz	7.6 dB/100m
540 MHz	10.1 dB/100m
1000 MHz	14.3 dB/100m

Electricals

Nom. Conductor DCR	Nom. Inner Shield DCR	Nom. Outer Shield DCR	Nom. Capacitance Cond-to-Shield	Nom. Characteristic Impedance	Nom. Velocity of Prop.
5.7 Ohm/km	6.4 Ohm/km (2.0 Ohm/1000ft)	4.1 Ohm/km (1.2 Ohm/1000ft)	55 pF/m (17 pF/ft)	75 Ohm	81%

Screening

Frequency	Min. Screening Attenuation
30 - 850 MHz	75 dB

Mechanical Characteristics

Temperature

Operating	Installation	Storage
-40°C To +70°C	-5°C To +70°C	-40°C To +70°C

Bend Radius

Stationary Min.
150 mm (5.9 in)

Max. Pull Tension:	550 N (120 lbf)
Bulk Cable Weight:	237 kg/km

Standards and Compliance

Environmental Suitability:	Indoor (Not Riser or Plenum)
European Directive Compliance:	EU CE Mark

History

Update and Revision:	Revision Number: 0.205 Revision Date: 06-25-2024
----------------------	--

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.